








# WING NUTS

Technical specifications  
based on zinc

Product	Dynacast Part Number	Blank Size	Thread Sizes	Wing Spread	Overall Height	Approximate Ship Weight Lbs/M
<b>Washer Base</b> 	232 300	AEW	6-32, 8-32, 10-24, 10-32	3/4	23/64	3.0
	232 400	BEW	1/4-20, 8-32, 10-24, 10-32	7/8	7/16	5.9
	232 500	CEW	1/4-20, 5/16-18	1	1/2	9.0
	232 600	DEW	1/4-20, 3/8-16, 5/16-18	1-1/8	37/64	14.8
<b>Senior</b> 	222 200	AA	4-36, 4-40, 5-40, 6-32	.650	.355	3.5
	222 300	A	6-32, 8-32, 10-24, 10-32, 12-24	.840	.425	7.0
	222 400	B	1/4-20, 1/4-28, 12-24	1-1/16	38/64	10.5
	222 500	C	1/4-20, 5/16-18, 5/16-24	1-7/32	.630	14.0
	222 600	D	3/8-16, 3/8-24	1-7/16	.730	23.0
	222 700	E	7/16-14, 7/16-20, 1/2-13, 1/2-30	1-7/8	.906	53.0
<b>Junior</b> 	223 200	AAL	4-40, 6-32	5/8	19/64	2.5
	223 300	AL	6-32, 8-32, 10-24, 10-32	3/4	11/32	3.2
	223 400	BL	1/4-20, 8-32, 10-24, 10-32	7/8	7/16	5.5
	223 500	CL	1/4-20, 5/16-18	1	1/2	8.0
<b>Economy</b> 	224 300	AE	6-32, 8-32, 10-24, 10-32	3/4	11/32	2.5
	224 400	BE	1/4-20, 8-32, 10-24, 10-32	7/8	27/64	4.5
	224 500	CE	1/4-20, 5/16-18, 10-24, 12-24	1	31/64	6.5
	224 600	DE	1/4-20, 3/8-16	1-1/8	9/16	10.0
<b>High</b> 	225 300	HA	8-32	29/32	11/16	10.0
	225 400	HB	1/4-20, 10-24, 10-32	1-1/8	27/32	17.0
	225 500	HC	1/4-20, 5/16-18	1-9/32	1-1/32	26.0
	225 600	HD	3/8-16	1-1/2	1-3/16	42.0
<b>Low</b> 	226 300	LA	6-32	13/16	.240	3.5
	226 400	LB	1/4-20, 8-32, 10-24, 10-32	1	.277	7.0
	226 500	LC	1/4-20, 10-24, 12-24	1-3/16	.315	10.0
	226 600	LD	5/16-18	1-3/8	.353	17.0
	226 700	LE	3/8-16	1-7/8	.562	26.0
<b>Low Washer Base</b> 	233 400	SLB	6-32, 8-32, 10-24, 10-32	1-1/32	9/32	8.0

**Custom Wing Nuts:** Many customs on hand, or can be produced to meet your specifications.

**ULTRA-Economy Wing Nuts:** Using our exclusive "Single Thread" design, we can eliminate costly tapping operations.

**Serrated Base Wing Nuts:** Most Wing Nut blanks can be supplied with tooth like serrations on the base, quantity and scheduling permitting.